

### Listing of the Claims:

The following is a complete listing of all the claims in the application, with an indication of the status of each:

1 (Original). An electrode assembly for the electrochemical treatment of liquids with a low conductivity, said assembly having electrodes (1, 2) which have a polymeric solid electrolyte (3) arranged between them, are pressed against one another by means of a pressure-exerting device (9, 10; 91) and are formed in such a manner that the liquid can flow through the assembly, characterized in that the pressure-exerting device (9, 10; 91) is supported on the electrodes (1, 2).

2 (Original). The electrode assembly as claimed in claim 1, characterized in that at least one electrode (1, 2) has a support which is coated with a doped diamond layer.

3 (Original). The electrode assembly as claimed in claim 2, characterized in that the support comprises metal.

4 (Original). The electrode assembly as claimed in claim 3, characterized in that the support is formed from an expanded metal grid (11, 21).

5 (Currently Amended). The electrode assembly as claimed in claim 2 or 3, characterized in that the electrodes (1, 2) have passage openings (42) to the polymeric solid electrolyte (3).

6 (Currently Amended). The electrode assembly as claimed in ~~one of claims 1 to 5~~ claim 1, characterized in that the solid electrolyte (3) has

passage openings.

7 (Currently Amended). The electrode assembly as claimed in ~~one of~~  
~~claims 1 to 6~~ claim 1, characterized in that the polymeric solid electrolyte (3)  
only partially fills the interspace between the electrodes (1, 2).

8 (Original). The electrode assembly as claimed in claim 7, characterized  
in that the polymeric solid electrolyte (3) is arranged in strips, which are at a  
distance from another, in the interspace between the electrodes (1, 2).

9 (Currently Amended). The electrode assembly as claimed in ~~one of~~  
~~claims 1 to 7~~ claim 1, characterized in that the polymeric solid electrolyte (3)  
is arranged in area pieces (33), which are at a distance from one another on  
all sides, in the interspace between the electrodes (1, 2).

10 (Currently Amended). The electrode assembly as claimed in ~~one of~~  
~~claims 1 to 9~~ claim 1, characterized in that the polymeric solid electrolyte (3)  
is applied to one of the electrodes (2) as a surface layer.

11 (Currently Amended). The electrode assembly as claimed in ~~one of~~  
~~claims 1 to 10~~ claim 1, characterized in that it is formed from a stack of a  
plurality of electrodes (1, 2) and a plurality of polymeric solid electrolytes (3)  
which are arranged between two respective electrodes (1, 2), said electrodes  
and electrolytes being jointly pressed against one another by the pressure-  
exerting device (9, 10).

12 (Currently Amended). The electrode assembly as claimed in ~~one of~~

~~claims 1 to 10~~ claim 1, characterized in that a plurality of individual assemblies which are formed from two respective electrodes (1, 2) and one polymeric solid electrolyte (3) are connected to the pressure-exerting device (9, 10) to form a stack.

5

13 (Currently Amended). The electrode assembly as claimed in ~~one of claims 1 to 12~~ claim 1, characterized in that the electrodes (1, 2) are flat.

10

14 (Currently Amended). The electrode assembly as claimed in ~~one of claims 1 to 13~~ claim 1, characterized in that the pressure-exerting device (9, 10) comprises a plurality of screw connections which are led through the electrodes and are made of insulating material.

15

15 (Currently Amended). The electrode assembly as claimed in ~~one of claims 1 to 13~~ claim 1, characterized in that the pressure-exerting device (91) is formed from material which is in the form of a wire, is wrapped around the electrodes (1, 2) and has ends which are twisted together in order to generate the pressure.

20

16 (Currently Amended). The electrode assembly as claimed in ~~one of claims 1 to 12 and 15~~ claim 1, characterized in that two electrodes (1, 2) are in the form of rods, and in that the polymeric solid electrolyte (3) in the form of a strip (34) alternately wraps around the electrodes (1, 2) under prestress.